National Bureau of Standards Emers Amilier, Director

# National Bureau of Standards

## **Tertificate**

## Standard Reference Material 4370C

### Radioactivity Solution Standard

Radionuclide Europium-152

Source identification 4370C

Liquid in 5-mL flame-sealed glass ampoule (1)\* Source description

Source mass 5.0338 ± 0.0019 grams (2)

277 ug Eu per gram of 1 M HCl Solution composition

9.390 x 10<sup>4</sup> Bq g<sup>\*1</sup> Radioactivity concentration

> 1200 EST February 2, 1987 Reference time

1.1 percent (3) Overall uncertainty

154 Eu / 152 Eu:  $(2.9 \pm 0.3) \times 10^{-3}$  (4) Photon-emitting impurities

(activity ratio at reference time)

13.55 ± 0.06 years (5) Half life

Measuring instrument 4my pressurized ionization-chamber

"A" previously standardized by 4my counting with the NBS 8"x8" NaI(T1)

crystals

This Standard Reference Material was prepared in the Center for Radiation Research, Ionizing Radiation Division, Radioactivity Group, Dale D. Hoppes, Group Leader.

Gaithersburg, MD 20899 March, 1987

Stanley D. Rasberry, Chief Office of Standard Reference Materials

<sup>2</sup>Notes on back

#### NOTES

(1) Approximately five milliliters of solution. Ampoule specifications:

body diameter	16.5 ± 0.5 mm
wall thickness	$0.60 \pm 0.04 \text{ mm}$
barium content	less than 2.5 percent
lead oxide content	less than 0.02 percent
other heavy elements	trace quantities

- (2) The standard deviation is 0.0019 grams based on mass measurements of 15 ampoules.
- (3) The overall uncertainty was formed by taking three times the quadratic combination of standard deviations of the mean, or approximations thereof, for the following:

a)	1987 ionization-chamber	
	measurements on 17 sources	0.02 percent
ь)	original ionization-chamber	-
	calibration using 7 sources	0.08 percent
c)	ratio of radium reference	•
	sources	0.05 percent
d)	solution attenuation of	-
	y-rays	0.10 percent
e)	gravimetric measurements	0.15 percent
f)	impurities	0.10 percent
8)	decay correction	0.02 percent
h)	NaI(T1) measurements on	•
	6 sources	0.02 percent
5)	NaI(Tl) detector efficiency	0.27 percent
j)	fluorescence yield	0.10 percent
	Combined	0.37 percent
		<u>x 3</u>
	Overall	1.1 percent

- (4) The limit of detection, expressed as a percentage of the gamma-rayemission rate of the 1408-keV gamma rays emitted in the decay of europium-152, is
  - 0.1 percent between 90 and 1900 keV,

provided that the impurity photons are separated in energy by 5 keV or more from photons emitted in the decay of europium-152 and europium-154.

(5) NBS-measured half-life value. NCRP Report No. 58, 2nd edition, 1985, p. 464 lists a value of 13.4 ± 0.1 years.

For further information please contact Ms. J.M. Calhoun at (301) 975-5538 or Dr. Bert M. Coursey at (301) 975-5539.